

## Nixon

<b>Tuft gauge</b>	1/10 cut pile	ISO 2424
<b>Pilecomposition</b>	100% PA SDN	ISO 2424
<b>Primary Backing</b>	Woven	ISO 2424
<b>Secondary backing</b>	AB	ISO 2424
<b>Width</b>	400 cm, 500 cm ± 1%	EN 986
<b>Pile Weight</b>	1100 gr/m <sup>2</sup>	ISO 8543
<b>Total weight</b>	1875 gr/m <sup>2</sup> ± 15%	ISO 8543
<b>Pile height</b>	7 mm	ISO 1765
<b>Total Height</b>	9 mm	ISO 1765
<b>Number of knots</b>	177.300/m <sup>2</sup> -7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Cfl-S1	EN 13501-1
<b>Use Area</b>	Medium project use (32)	EN 1307
<b>Light fastness</b>	≥ 5	105-B02
<b>Wearebility</b>	≥ 4	105-X12
<b>Water fastness</b>	≥ 4	105-E01
<b>Electrostatic charging</b>	<2 kV	ISO 6356
<b>Luxury class</b>	LC4	EN 1307
<b>Pictures</b>	www.condorcontract.com	

## Floorsymbols



## Certificates



www.blauer-engel.de/uz128

