

QUALITY  
ORDER CODE

DATE: **7/03/2016**  
REPLACES: 7/03/2016

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
WOOLMARK  
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (± 15%) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE  
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

**PANORAMA**

± 400  
COLLECTION  
1/10" CUT PILE

PIECE DYED

PA

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 600  
± 1.740

± 3,5  
± 6,0  
± 189.120  
± 39,40  
± 48,00

±  
±

±

✓  
✓  
✓  
✓  
✓  
✓  
✓  
✓

✓

Cl. 32  
Commercial General



LC1



Bfl-s1



QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 10



SOUND ABSORPTION

(±)

$\alpha_s$

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

$\alpha_w$

EN ISO 11654

±

THERMAL RETENTION

(±) m<sup>2</sup>/KW

ISO 8302

± 0,11

TOG rating

(±)

± 1,1

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

<

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



0493-CPR-1038-123668

EN 14041



EN 1307

ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SB/FS 400

**OPS**

- 010 TULIPWOOD
- 100 RUBY
- 120 CORAL
- 200 CHOCOLATE
- 220 ACORN
- 250 MAGNOLIA
- 260 CAMEL
- 690 SATIN JADE
- 720 BLUE CAPE
- 770 SAPPHIRE
- 790 MIDNIGHT
- 800 EBONY
- 820 SLATE
- 830 ASH
- 840 MOONSHINE

SB/FS 400

**OPS**

